



# KD SERIES

## Ovens



- Suitable for drying, warming and heating, heat treatment and long term stability tests in research and industrial laboratories
- Very homogeneous temperature distribution by forced air ventilation
- Extraction fan for faster drying
- High grade insulation for efficient heating and temperature stability
- Stainless steel chamber which has high resistance to most of the chemicals
- The door, pressing firmly and tightly on the chamber gasket to reduce temperature loss
- Adjustable outlet port for vapour exhaustion
- User friendly, programmable, reliable, accurate PID microprocessor control system
- Programmable delayed start function
- Highly visible dual displays for temperature and time
- Adjustable independent safety thermostat which takes over control in case of any failure

## TECHNICAL SPECIFICATIONS

	KD 200	KD 400	KD 700
Temperature Range	70°C / 250°C		
Temperature Sensor	Fe-Const		
Control System	Programmable Microprocessor		
Temperature Set and Display Sensitivity	1°C		
Temperature Variation @150°C	± 4°C		
Temperature Fluctuation	± 2°C		
Timer	1 minute – 99,9 hours + Hold Position		
Delayed Start Timer	1 minute – 99,9 hours		
Useful Volume, litres	193	375	700
Number of Shelves (Standard/ Max.)	2/7	2/12	
Internal Material	Stainless Steel		
External Material	Epoxy - Polyester Powder Coated Steel		
Power Consumption	3100 W	4100 W	8200 W
Power Supply	400 V, 3 phases+N+G 50/60 Hz		
Internal Dimension (WxDxH) mm	500x450x850	500x575x1350	995x575x1350
External Dimension (WxDxH) mm	690x690x1120	690x790x1620	1150x820x1720
Packing Dimension (WxDxH) mm	730x760x1320	760x830x1850	1220x920x1950
Net / Packed Weight kg.	90 / 112	140 / 160	210 / 280

## ACCESSORIES

- R 01 111 Mesh type shelf for KD 200  
R 01 134 Mesh type shelf for KD 400  
R 01 111 S.S shelf for KD 700  
K 23 040 Shelf carrier for KD 200/400  
K 23 030 Shelf carrier for KD 700

Note: 2 pcs. shelf carrier should be ordered for each shelf



**NUVE SANAYİ MALZEMELERİ İMALAT VE TİCARET A.Ş.**

Saracalar Mah. Saracalar Kümeevleri No: 4/2 Akyurt 06750 ANKARA / TURKEY t. +90 312 399 28 30 f. +90 312 399 21 97

[nuve.com.tr](http://nuve.com.tr) [sales@nuve.com.tr](mailto:sales@nuve.com.tr)

ISO 9001: 2008  
ISO 13485: 2003